



**Security
Care
Limited**

Reach us on
0121 445 2587

• **Established 1995** •



CONTRACTORS HEALTH & SAFETY ASSESSMENT SCHEME
Accredited Contractor
www.chas.gov.uk

DEMON LPS 1175 SR4 Doors



Our LPS 1175 SR4 Door has been engineered to provide the ultimate in security for high security applications. Currently this door has been installed widely on MoD sites and as of October 2016 has yet to be successfully breached. Installing a secure steel door provides an excellent way of securing a building from a break in. A key advantage with steel being that it will not splinter and therefore weaken when attacked as with timber doors.

From placement of order we can normally turnaround doors within 4-5 weeks from placing the order to delivering it direct to site. The doors are available with a variety of locking options including panic, manual and electromechanical deadlocking hardware. Due to the testing you are unfortunately limited to the hardware which has been successfully tested with the doors to achieve certification.

Unlike many of our competitors we exclusively supply British Manufactured products so you can be confident that our doors are of the highest quality. Furthermore the SR4 has been independently tested by the LPCB to ensure that it will keep your building secure.

Testing for LPS 1175 SR4

Products certified to LPS 1175 SR4 standard provide up to 10 minutes of resistance to experienced attempts at forced entry using a wide range of tools, including: high powered cordless tools, felling axe, sledgehammer, power drill, disc grinder, jigsaw, etc.

Key Points:-

- Available as inwards (single doors only) or outwards opening .
- Can be Fire Rated if necessary.
- Bladed Louvre Cartridges can provide ventilation
- Vision Panels can also be fitted
- Doors weigh circa 75kg m²
- Independently Tested & Certified

Please ask a sales advisor regards being supplied a steel door manufactured from Magnelis

Certified Sizing (Structural Opening Sizes):-

Single Outward Opening Doorsets: 600mm to 1430mm wide & 1000mm to 2930mm high
Double Outward Opening Doorsets: 900mm to 2600mm wide & 1000mm to 2930mm high
Single Inward Opening Doorsets: 600mm to 1430mm wide & 100mm to 2430mm high

Specification

Door Frame

- Manufactured from 2.0mm Zintec Steel
- 3mm Chassis System (no adjusters)
- 110mm deep single rebate profile

Threshold

- DDA compliant threshold

Door Leaf

- Outerskins manufactured from 1.5mm Zintec steel
- Folded 66mm thick leaf with internal plating to suit lock requirements
- Integral Anti Jemmy Strip to protect against crowbars (10mm).

Security Door Hinges

- Minimum of 6 126mm Lift off Stainless Steel Hinges per leaf.

Security Dog Bolts

- Minimum of 9 no. Hooked Solid Steel Dog Bolts per leaf.

Contact Information

313 Old Birmingham Road, Marlbrook, Bromsgrove, Worcestershire, B60 1HQ

Tel: 0121 445 2587 / Fax: 0121 445 2551

E-mail: sales@securitycare.co.uk / Website: www.securitycare.co.uk

Security Care Ltd. Registered in England 4449222

